

PATURA

GSM-Steckdose • Prise secteur GSM • GSM Power Socket • GSM-stopcontact

Ref. 156311

GSM

2G Dual-band 900/1800 MHz

Netzstrom / Courant / Power Input / Netroom

AC110-250V/50Hz

Max. Stromaufnahme / Consommation de courant max. /

Maximum Load / Max. stroomverbruik

250V / 16A

Betriebstemperatur / Température de fonctionnement /

Operating temperature / Bedrijfstemperatuur

-20°C - +60°C

Lagertemperatur / Température de stockage /

Storage temperature / Opslagtemperatuur

-20°C - +70°C

Schutzklasse / Norme IP / Protection Class / Beveiligingsklasse

IP20 nur Inneneinsatz / IP20 utilisation intérieure uniquement /

IP20 only internal operation / alleen binnen gebruik

Temperatur Sensor Kabellänge / Longueur du câble

thermomètre / Temperature Sensor Cable Length /

Kabellänge temperatuursensor

3m

Temperatur Sensor Bandbreite / Champ du capteur de

température / Temperature Sensor Range / Bandbreedte

temperatuursensor

-20°C - +70°C

Genauigkeit Temperatursensor / Précision du capteur de

température / Temperature sensor accuracy /

Nauwkeurigheid temperatuursensor

±2°C




patura

**GSM-Steckdose
Prise secteur GSM
GSM Power Socket
GSM stopcontact
Ref. 156311**

**GARANTIE 3 ANS
3 YEAR WARRANTY
3 JAAR GARANTIE**



**Kurzanleitung
Guide rapide
Quick Guide
Snellhandleiding**

Lieferumfang
Contenu de la livraison
Included in delivery
Leveringsomvang

PATURA GSM-Steckdose
 Prise secteur GSM
 GSM Power Socket
 GSM stopcontact

Ref. 156311



Temperatursensor
 Capteur de température
 Temperature sensor
 Temperatuursensor

INSTALLATION



patura.luda.farm



PC/Mac



www.patura.luda.farm



Funktionen
Fonctions
Functions
Functies

USB Anschluss / Ohne Funktion
 Port USB / sans fonction
 USB port / no function today
 USB-aansluiting / Functioneer niet

GSM



Zurücksetzen
 Réinitialiser
 Reset
 Terugzetten

Manuell EIN/AUS
 Interrupteur manuel
 MARCHÉ / ARRÊT
 Manual ON/OFF
 Handmatig AAN/UIT